

D10M-36H-T

PRESSURE CLEANER

Diesel Driven - 10HP - MINE SPECIFICATION - 3625 PSI MPP - Hot Water

3625 PSI Max Pump Pressure 2600 PSI Setup Pressure









Heavy Duty - DIESEL - Hot Water - 3625 PSI, 15LPM

Heavy Duty Water Blasters - Portable, Skid, Trailer & Wash Bay Units



10HP Heavy Duty Mine Spec, 1000 litre IBC Trailer Mounted DIESEL PRESSURE CLEANER

The ideal trailer mounted water blaster that demands high pressure and/or flow in a rugged, tough and over-engineered machine, that will outlast any other water blaster!

MAX PUMP PSI 3625 PSI STANDARD SETUP PSI 2600 PSI FLOW/MINUTE 15 LPM

POWERED BY 10 HP YANMAR Diesel Engine SIZE 410 x 185 x 180 cm WEIGHT ~750 kg

POWER SOURCE

- Italian made 10 HP YANMAR Air Cooled Diesel Engine.
- Push-button electric start
- Exhaust spark arrestor -AS certified.
- Wired to shut down on low tank water level preventing pump from cavitating and running dry.
- Close coupled direct drive via 2:1 gearbox.

DELIVERY

- Heavy duty glycerinefilled pressure gauge rated to 10,000 PSI.
- Heavy duty galvanized hose reel (Lockable during travel).

30m R2 thick wall 3/8" HP Hose:

- Rated to 5000 PSI.
- 4x burst rating.
- Hose end sleeved for operator protection.

Italian made dry gun

- 900mm insulated stainless steel lance.
- Stainless steel fan nozzle.

PUMP

- HAWK NPM1525R Triplex Pump rated at 3625 PSI max @ 15
- The pump is de-rated** to 2600 PSI to prolong pump life.
- · Ceramic sleeved, stainless steel piston plunger rods and brass pump head.

FRAME

- Heavy duty 4x4 style, fully hot dipped galvanised trailer.
- Land Cruiser style six stud wheels on 2-ton axle with spare wheel.
- Mechanical disk brakes with manual hand brake
- LED side clearance lights and tail lights.
- Engine is vibration mounted on separate sub-frame.
- Stainless steel control box with hour meter & E-stop.

BY-PASS VALVE

• PSI K7-1 by-pass valve. Zero PSI stored downstream when in by-pass.

BOILER / BURNER

- S/S Vertical boiler with 1/2" mild steel coils, set
- Stainless steel fuel tank to boiler (23 litres).

SUPPLY

- Water supply is from onboard 1000L water tank, dual water intake with dual water filters to protect the pump from water debris.
- Tank with float switch to shut motor down on low water supply protects pump against cavitation & dry running - extending pump life.

MINE SPEC FEATURES

- Emergency-stop.
- Exhaust spark arrestor.
- Engine drip tray.
- 2kg Fire extinguisher.
- High Vis tape all round.
- Painted draw bar.
- Wheel nut indicators.
- Wheel chocks mounted.
- Lockable battery isolator.
- Ignition isolator.
- Covered batterybox.
- Double wire insulation.
- Anderson type jump-start receptacle.